

Diagram showing the unboxing process: opening the box, reading the manual, and discarding the packaging. A 'REQUIRED' section shows 5 screws and a mounting bracket. A dimension diagram shows the bracket length L and mounting hole positions M1, M2, and M3.

Ver.	D [mm]	L [mm]	M1 [mm]	M2 [mm]	M3 [mm]
mini	270	212	46	-	60
midi	360	311	55,5	-	100
maxi	440	395	30	107,5	60

**1** Tighten the top cap screw with a screwdriver.

**2** Insert the mounting bracket into the top cap.

**3** Attach the suspension cable to the bracket.

**4** Attach the mounting bracket to the ceiling using 2 screws. The diameter of the light fixture is D.

**5** Turn the power switch OFF. Drill holes (I) and insert screws (II) into the ceiling.

**6** Connect the power wires (L, N, PE) to the terminal block on the back of the fixture. Tighten the wire nuts.

**7** Turn the power switch ON. Attach the light source (I) to the fixture using a screwdriver (II) and a hex key (III).

**8** The final installation is complete. The power switch is ON.

Źródło światła zastosowane w tej oprawie oświetleniowej powinno być wymieniane wyłącznie przez producenta lub jego przedstawiciela serwisowego, lub podobnie wykwalifikowaną osobę.  
The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.



Ten produkt zawiera źródła światła o klasie efektywności energetycznej D.  
This product contains a light sources of energy efficiency class D.

**LED**  
int